### imagePROGRAF PRO-2100

# HIGH QUALITY PRINTING WITH ADVANCED IMAGE PROCESSING

A 24 inch printer that delivers high quality printing for the graphic, fine art, and print for pay markets, in a compact size.





#### Passcode printing

Set user print permissions and individual passcodes to restrict access and boost security

#### Automated processes

Smart media handling automatically detects the media type and estimates remaining media

#### Software solutions

Professional Print enables soft proofing, layout functions and pattern printing, on-screen

#### Operation efficiencies

Work more productively by saving settings for routine print tasks, on an individual level

#### Borderless print

Print various-sized borderless images from one roll size, with high margin adjustment accuracy



#### **PRODUCT RANGE**



imagePROGRAF PRO-2100



imagePROGRAF PRO-4100



imagePROGRAF PRO-6100



### **TECHNICAL SPECIFICATIONS**

## imagePROGRAF PRO-2100

TECHNOLOGY

Printer Type Print Technology

Print Resolution Number of Nozzles Line Accuracy

Nozzle Pitch

Ink Droplet Size

OS Compatibility

Printer Languages

Standard Interfaces

MEMORY Standard memory

PRINT TIME FOR A1 PAGE SIZE

Media Type Plain Paper

Hard Drive

Coated Paper

Glossy Photo Paper

MEDIA HANDLING Media Feed and Output

Media Width

Media Thickness Minimum Printable Length Maximum Printable Length

Maximum Media Roll

Media Core Size

Margins Recommended area

Margins Printable area

Media Feed Capacity

Media Take-up roll unit

12 Colour 24"/610mm

Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)

2.400 x 1200 dpi

18.432 nozzles (1536 nozzles x 12 colours)

±0.1% or less

User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only

 $600\ dpi\ x\ 2$  includes Non-firing nozzle detection and compensation system

minimum 4 pl per colour

Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 160ml

Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser

Microsoft Windows: 32 Bit, Vista, 7,8, 8.1,10 Server 2008, 64 Bit: Vista, 7,8, 8.1,10, Server 2008/R2, Server 2012/R2, Windows Server 2019 Apple Macintosh: OS X 10.11.6, macOS 10.12-macOS 10.15 SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)

USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0

Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

3 GB

500GB (Encrypted HDD)

Print Mode: Print Time

**Print Mode** Fast Standard Print Time 00:58 min 01:38 min Print Mode Print Time Standard High Quality 01:38 min 03:11 min **Print Mode** Print Time 03:11 min

Upper Roll Paper: One Roll, Front-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)

Roll paper: 152.4 - 610mm Cut sheet: 152.4 - 610mm

High Quality

170 mm

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

Maximum number of delivered prints

**DIMENSIONS AND WEIGHT** 

Physical Dimensions WxDxH (mm) and Weight (Kg)

Packaged Dimensions WxDxH (mm) and Weight (Kg)

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Certificates

WHAT'S INCLUDED

05:02 min

Roll/Cut: 0.07 - 0.8 mm

203.2 mm

Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 2133.6mm

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Roll Paper: Two rolls. Automatic switching is possible Cut Sheet: 1 sheet

Borderless Printing Width (Roll Only)

515mm(JIS B2), 594mm(ISO A1), 10", 14", 17", 24", 257mm(JIS B4)\*, 297mm(ISO A3)\*, 329mm (ISO A5+)\*, 420mm(ISO A2)\*, 6",8"\*, 12",16"\*, 20", 22", 30"\*, 300mm\*, 500mm, 600mm and custom roll width (154.2-610mm)

Some environmental conditions may not produce the desired result

Standard position: 1 sheet

Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets

Printer (Main unit with pallet): 1324 x 902 x 1042 mm

Operating Environment

Accoustic Noise

(Power/Pressure)

Regulations

What's in the Box?

Software Included

OPTIONS Optional Items

> CONSUMABLES User Replaceable Items

(excludes strong curled condition)

1110 x 984 x 1168 mm (Basket Open) 1110 x 766 x 1168 mm (Basket Closed) 119 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)

Printer (1. 3.... 124kg Roll Unit: 1244 x 562 x 461 mm 26kg

AC 100-240V (50-60Hz)

AC 100-240V (30-6012)
Operation: 93 W or less
Sleep mode: 2.0W or less
Default setting for the time to enter the Sleep mode:
Approx. 5 Minutes
Power off: 0.3 W or less

Temperature: 15~30°, Humidity: 10~80% RH (no dew condensation)

Operation: approx. 46 dB (A) (Glossy paper, Print priority: Standard) Standby: 35 dB (A) or less Operation: 6.4 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)

Europe: CE mark, Russia: EAC

Printer, Iprint heads, 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet

imagePROGRAF PRO Printer Driver and PosterArtist Lite Other software available as Download from Web.

Printer Stand: SD-21 2/3" Roll Holder: RH2-29 Roll unit: RU-23

Ink Tank: PFI-1100 (160ml), PFI-1300 (330ml), PFI-1700 (700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30

**Disclaimer**Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. The area of the many and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.







Canon Inc. canon.com

Canon Europe canon-europe.com

English edition © Canon Europa N.V.,2019

